



TVP-1000
TVP-2000

The Preferred Choice

for Thermal Printers



TVP-2000

TVP-1000

Multi-Purpose Thermal Printing

Thermal Printer

TVP-1000 TVP-2000

Model Specification

MAIN FEATURES

| | TVP-1000 | TVP-2000 |
|-------------------------|--|---|
| • Model | TVP-1000 | TVP-2000 |
| • Printing Method | Direct thermal | Direct thermal & thermal transfer |
| • Printing Resolution | 203 dpi (8 dots/mm) | 203 dpi (8 dots/mm) |
| • Max. Printing Speed | 3.5 ips (89mm/s) | 3 ips (76 mm/s) |
| • Max. Printing Length | 45" (1143mm) | 45" (1143mm) |
| • Max. Printing Width | 2.2" (56mm) | 4.13 (105mm) |
| • Fonts | 5 alpha-numeric fonts from 0.49" - 0.23" height (1.25 - 6mm) All fonts are expandable up to 24 x 24 4 directions 0° - 270° rotation Soft fonts are downloadable | 5 alpha-numeric fonts from 0.49" - 0.23" height (1.25 - 6mm) All fonts are expandable up to 24 x 24 4 directions 0° - 270° rotation Soft fonts are downloadable |
| • Barcodes | Code 39, Extended Code 39, Code 93, Code 128 (Subset A,B,C), Codabar, Interleave 2 of 5, EAN-8 2&5, EAN-13, EAN-128, UPC, UPC-A, E 2&5, Matrix 10 | Code 39, Extended Code 39, Code 93, Code 128 (Subset A,B,C), Codabar, Interleave 2 of 5, EAN-8 2&5, EAN-13, EAN-128, UPC, UPC-A, E 2&5, Matrix 10 |
| • 2D Barcodes | Maxicode, PDF-417, Datamatrix | Maxicode, PDF-417, Datamatrix |
| • Graphic | PCX bit map, GDI graphics | PCX bit map, GDI graphics |
| • Memory | 512K standard | 512K standard |
| • Interfaces | RS-232 serial, centronics | RS-232 serial, centronics |
| • Media | Roll-feed, die-cut, continuous, fan- fold, tags, tickets in thermal paper Width 1" - 2.36" (25 - 60mm) Length 0.4" - 45" (10 - 1143mm) Supply roll - Outer diameter 5" (127mm) - Inner diameter 1" (25mm) | Roll-feed, die-cut, continuous, fan- fold, tags, tickets in thermal paper Width 1" - 4.3" (25 - 110mm) Length 0.4" - 45" (10 - 1143mm) |
| • Ribbon | Nil | Wax, Wax/Resin, Resin Standard width - 1.3", 2.5", 3.3", 4.4" - 33mm, 64mm, 84mm, 109mm Ribbon roll - Outer diameter 1.4" (36mm) - Inner diameter 0.5" (12.5mm) |
| • Compact Size | 5.3" (W) x 9.0" (D) x 6.4" (H) 134 (W) x 228 (D) x 163 (H) mm | 7.3" (W) x 10.9" (D) x 6" (H) 186 (W) x 278 (D) x 153 (H) mm |
| • Weight | 2.6 lbs (1.2 kg) | 4.6 lbs (2.1 kg) |
| • Power Source | 110 / 220 VAC +/- 10%, 50/60 Hz | 110 / 220 VAC +/- 10%, 50/60 Hz |
| • Approvals | CE, UL, CUL, FCC, CLASS A | CE, UL, CUL, FCC, CLASS A |
| • Operation Environment | 40° F - 100° F (4 - 38° C), 10 - 90% Non-condensing | 40° F - 100° F (4 - 38° C), 10 - 90% Non-condensing |
| • Software | Label editing software - Digi X-bar & printer driver | Label editing software - Digi X-bar & printer driver |

OPTIONS

- Cutter, dispenser kit, extension flash memory

* Specifications are subject to change without notice.

TERAOKA SEIKO CO., LTD

13 - 12 Kugahara 5-chome, Ohta-ku,

Tokyo 146-8580

Japan

TEL: +81-3-3752-2131

FAX: +81-3-3752-2801

EMAIL: info@hq.digi.co.jp

WEBSITE: <http://teraoka.digi.co.jp/index.nsf>

TERAOKA WEIGH-SYSTEM PTE LTD

4 Leng Kee Road #05-03/04/05

SIS Building Singapore 159088

TEL: (65) 472 2996

(65) 378 5388 (Sales)

FAX: (65) 472 2869

EMAIL: sales@teraoka.com.sg

WEBSITE: <http://www.teraoka.com.sg>