

## EP3GD

Stainless steel scales "Easy Pesa 3GD" series, for ATEX zones 2 and 22



Fully stainless steel bench scales, for specific use in ATEX hazardous areas. Powered by a long lasting rechargeable battery which allows an easier installation directly where it's needed. These scales don't need a power supply socket in dangerous zone nor ATEX proof power supply cables. Provided with ATEX declaration of conformity. Ex II 3GD IIC T6 T130°C X protection.

The best solution  
for advanced industrial  
applications

## PLATFORM FEATURES

- Approved "single point" STAINLESS STEEL load cell according to OIML R60 standards with protection against dust and water splashes according to IP67 standards.
- ATEX approved load cell with ATEX protection:  
ATEX II 1G Ex ia IIC T6 (Ta -20÷+40°C) TX (Ta -20÷+65°C) Ga.  
ATEX II 1D Ex ta IIIC TX°C (Ta -20÷+40°C) TX°C (Ta -20÷+65°C) Da IP65
- Structure, enclosure and loading plate made in AISI304 stainless steel.
- Adjustable levelling feet with plastic over shoe.
- Supplied with support column, height:
  - 500 mm in the "Q" models;
  - 700 mm in the "X" models.

## WEIGHT INDICATOR FEATURES

- IP68 Weight indicator for ATEX areas with protection methods according to:  
ATEX II 3G Ex nR IIC T6 Gc X for gases.  
ATEX II 3D Ex tc IIIC T130°C Dc IP68 X for dust.
- EC-Type-Examination certificate according to Annex III (ATEX directive). CE-M approvable (OIML R-76 / EN 45501).
- Waterproof 17-key numerical and functional keyboard.
- Backlight LCD display with 6 25-mm high contrast digits, clearly visible even in poor lighting conditions and with low temperatures.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 µV/d in CE-M approved version for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- A/D 24-bit sigma-delta conversion, up to 200 conv./sec. autoselect.
- Power supply through external battery pack with 100h operating time. It's possible to buy another battery pack for continuous use (24/7).
- Charger included in the supply.

## SCALE FUNCTIONS

- SCALE FUNCTIONS
- Zeroing
- Automatic tare
- Presetable tare
- Selectable function command
- On/off switching.

### SELECTABLE FUNCTIONING MODE

- High Resolution Weighing x 10
- Net/Gross or lb/kg conversion
- Weight totalization
- Formula weighing
- +/- Checkweighing
- Counting (Max. resolution of 1.500.000 divisions)

## DETAIL 1

## DETAIL 2



### DETAIL 3



### VERSIONS

Versioni disponibili

Codice	Piatto Max (mm)	Max (kg)	d (g)	<b>M</b> (g)*	<b>M</b> 2R (g)*	d HR (g)*
EPQI3GD15B	400x400	15	2	5	2/5	1

EPQI3GD30B	400x400	30	5	10	5/10	2
EPQI3GD60B	400x400	60	10	20	10/20	5
EPQI3GD150B	400x400	150	20	50	20/50	10
EPXI3GD60B	600x600	60	10	20	10/20	5
EPXI3GD150B	600x600	150	20	50	20/50	10
EPXI3GD300B	600x600	300	50	100	50/100	20



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING”

**DINI ARGEO**  
**FRANCE** sarl  
Nogent-sur-Marne  
info.fr@diniargeo.com

**DINI ARGEO**  
**GMBH**  
Sinsheim - Germany  
info.de@diniargeo.com

**DINI ARGEO**  
**UK Ltd**  
Taunton - United Kingdom  
info.uk@diniargeo.com

**DINI ARGEO WEIGHING**  
**INSTRUMENTS Ltd**  
Shanghai - China  
info.cn@diniargeo.com

**DINI ARGEO**  
**WEIGHBRIDGES**  
Calto (RO) – Italy  
info@diniargeo.com



**HEAD OFFICE**

Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena - Italy  
Tel. +39.0536 843418 Fax. +39.0536 843521  
info@diniargeo.com

**SERVICE ASSISTANCE**

Via Dell'Elettronica, 15  
41042 Spezzano di Fiorano Modena - Italy  
Tel. +39.0536 921784 Fax. +39.0536 926654  
service@diniargeo.com



SALES AND TECHNICAL ASSISTANCE SERVICE